

INTELLIO



ILO-481-TR-DL Panoramic Turret camera, 8MP

NEO Multi

Made in Japan / NDAA certified

Camera

Image Sensor	Dual 1/2.8" Progressive Scan CMOS
Max Resolution	8MP, 4224(H) × 1848(V)
Shutter Speed	1/5 to 1/100,000s
Min Illumination	Color: 0.01 Lux @ (F1.6,AGC ON) B/W: 0.001 Lux @ (F1.6,AGC ON), 0 Lux with illuminator on
Day & Night	Auto (ICR)
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°

Lens

Lens Type	Fixed-focal lens, Dual lens
Focal Length	2.4 mm
Max. Aperture	F1.6
Field of View (FOV)	H: 192.4°, V: 80.2°
Iris	Fixed Iris

DORI Distance (EN62676-4 standard)

Detect	53 m (173.9 ft)
Observe	21.2 m (69.6 ft)
Recognize	10.6 m (34.8 ft)
Identify	5.3 m (17.4 ft)

Illuminator

Type	IR, Warm light (Smart Dual-light)
IR wavelength	850 nm
Distance	IR distance up to 30 m (98.4 ft) Warm light distance up to 20 m (65.6 ft)
Control	IR mode, White mode, Intelligent mode, None

Intelligent Analytics

AI Multi-Target	Supports face, human, and vehicle detection & capture Supports human and vehicle attribute detection Supports multiple frame modes: Full Frame, Four-Corner Frame, Mosaic
Attribute Extraction	Human Attributes: Gender, age, glasses, hat, bag, upper clothing color & style, lower clothing color & style, reflective vest Vehicle Attributes: Type, color, brand, orientation
Intelligent Analysis	Intrusion, smart motion detection, single line crossing, double line crossing, loitering, wrong-way detection, area people limit, perimeter detection, illegal parking, running detection, fall detection, and fight detection Supports accurate target classification (human/vehicle)
People Counting	Supported
Heat Map	Supported

Video & Audio

Number of Streams	3 Streams
Resolution	Splicing mode: - Stream1: 4224×1848, 3072×1760, 3072×1536, 2880×1440, 2560×1280, 2048×1024, - Stream2: 1920×832, 1536×576, 960×416, - Stream3: 1920×832, 1280×560, 960×416. Multi-channel mode: - Stream1: 2592×1944, 2592×1520, 1920×1080, 1280×720, - Stream2: D1, VGA, CIF, QVGA - Stream3: VGA, CIF, QVGA
Frame Rate	Up to 25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Splicing mode: - Stream1: 500 Kbps to 16 Mbps - Stream2: 200 Kbps to 8 Mbps - Stream3: 200 Kbps to 8 Mbps Multi-channel mode: - Stream1: 200 Kbps to 16 Mbps - Stream2: 100 Kbps to 6 Mbps - Stream3: 100 Kbps to 3 Mbps
Smart Encoding	Supported
Region of Interest (ROI)	Off / On (8 Zone, Rectangle)
Audio Compression	G.711 A-law, G.711 μ -law, RAW_PCM
Audio Bit Rate	64 Kbps (G.711), 128 Kbps (RAW_PCM)

Image

Image Adjustment	Brightness, Sharpness, Contrast, Saturation adjustable
Scene Mode	Indoor, Outdoor
Exposure Mode	Auto, Manual, Shutter priority
White Balance	Auto, Tungsten, Fluorescent, Daylight, Shadow, Manual
Day/Night Setting	Auto, Day, Night, Timer
Noise Reduction	2D/3D DNR
Image Enhancement	WDR, HLC, BLC, Defog
Wide Dynamic Range	True WDR (120dB)
Privacy Masking	4 areas

Event

Alarm Triggers	IVS, Motion detection, Alarm input, Network alarm, Disk alarm, Day/Night switch alarm, Abnormal sound detection
Event Actions	Alarm record, Alarm output, FTP upload, SMTP upload, Audible alarm output, White light alarm output, Red and blue light alarm

Network

Protocols	IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTCP/RTP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast
Application Programming Interface	ONVIF (Profile S/T/G/M), SDK, CGI
Max Concurrent Streams	10 channels
User/Host Level	32+ users, 3 levels: Administrator, Operator, Media user
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge



Security

OS / Firmware Protect	Encrypted firmware, Signed firmware
User Authentication	Digest authentication, Prevent brute-force attack
Network Authentication	IEEE 802.1X (EAP-TLS)
Secure Communication	HTTPS, WSS (WebSocket Secure), SRTP
Access Control	IP-based access control, Auto logout
Data Protect	Encryption credentials
Audit	Access / System / Event Log management
Secure Storage	SDcard partition encrypt (AES-256), Secure element
Supply Chain Security	SBOM

Interface

Network Interface	1 × Ethernet (10/100 Base-T), RJ-45 connector
Built-in Microphone	Supported
Built-in Speaker	Supported
Audio Interface	1ch Input, 1ch Output
Alarm Interface	1ch Input, 1ch Output
SD Card Slot	Built-in microSD card slot, up to 1 TB
Reset Button	Supported

General

Language	English (default), Chinese, Traditional Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian, Japanese, Korean
Power Supply	12VDC (-15% to +25%) / PoE (802.3af)
Power Consumption	Typical: 4.2 W (12 VDC) / approx. 5.3 W (PoE) Max. (IR on + Red/Blue light + Speaker): 8.9 W (12VDC) / approx. 11.2 W (PoE)
Operating Temperature	-40°C to 60°C (-40°F to 140°F)
Operating Humidity	Less than 95% RH
Ingress Protection	IP66
Certifications	CE-EMC - EN 55032, EN IEC 61000-6-4, EN IEC 61000-3-2, EN 61000-3-3, EN 55035, EN 50130-4 FCC 47 CFR Part 15 Subpart B
Material	Aluminum alloy body, Decoration ring: plastic
Dimensions	Φ140 × 119.2 mm (φ5.51 × 4.69 inch)
Net Weight	Approx. 0.93 kg (2.05 lb)
Accessories (optional)	
Junction box	 ILA-106
Vertical pole mounting bracket	 ILA-302

Dimensions (mm)

